

GLUING GUIDE



IMPORTANT – PLEASE READ BEFORE DECIDING IF YOU NEED TO GLUE OR LOOSE LAY YOUR FLOOR TILES

WOW Shelving's Heavy Duty Garage Floor Tiles have been designed to be installed as a loose-lay system, meaning that adhesive is not normally required. The interlocking design allows for quick installation and will give a professional clean appearance.

However in certain situations, using an adhesive will help improve the performance of the tile. We recommend using Mapei Adesilex G19 which has been specially formulated for use with PVC tiles like ours and offers a best in class performance.

We recommend using an adhesive in the following situations:

- **Exposure to Heat or Sunlight**

Areas affected by direct sunlight or heat sources (such as doors, windows, skylights, heaters, or hot pipes) may experience uneven expansion or contraction.

- **Heavy Loads or Vehicle Traffic**

Environments where forklifts, pallet trucks, or similar equipment are used—especially where loads are concentrated on small contact points.

- **Tight Turning Areas**

Locations where vehicles frequently turn in tight spaces, such as at the end of racking aisles.

- **Repetitive Traffic Routes**

Areas where traffic follows the same path repeatedly (for example, automated vehicles), which may cause tiles to shift over time.

- **Wet or Spill-Prone Areas**

Spaces exposed to repeated water, oils, or other liquids. Adhesive may help reduce liquid seepage through joints, but: The floor will not be fully waterproof or seamless, and no guarantee can be given against liquid penetration.

Please note: These examples are provided as guidance only and do not cover every possible application.

Use this advice in conjunction with the adhesive manufacturer's data sheets and relevant MSDS